



Description

Taubmans Endure Interior is engineered with Nanoguard. It has an interlocking molecular structure that works to create a protective shield, so stains can be wiped away without compromising the quality of the paint or damaging the finish on your walls. It provides excellent mould and mildew protection throughout the life of the paint so you will have a cleaner and healthier home environment. This is why Taubmans Endure is the only interior paint with a 15 year guarantee*.

Uses

All interior walls.

Recommended for

Superior performance

Features

Taubmans Endure has a unique interlocking molecular structure that creates a protective shield so that dirt and stains can simply be wiped away without compromising the quality of the paint.

Fungicide Protection

Resists mould and mildew growth.

Interlocking molecular structure

Protects against stains and regular washing.

Nanoguard

Engineered to Endure with a 15 year warranty.

Technical

Colour Range

Extensive colour range. Refer Taubmans to Consumer or Architectural/Specifier Colour Systems.

Drying And Recoating

Normally dries in 30 minutes and may be recoated after 2 hours (at 25°C and 50% relative humidity). Note - Drying time may be lengthened in damp, cold or humid conditions.

Gloss Level

Semi gloss (25%) as per AS2311

Specifications met

AS3730.2

Washability

Superior.

VOC

42 g/litre

Surface Preparation

Surfaces to be painted must be clean and dry.

New/Bare Work

Seal bare wallboards with Taubmans 3in1. Seal set plaster with Prep Right (Acrylic) Plaster Sealer.

Repaint

Remove all loose and flaking paint. Wash off dirt, grease. Fill holes and cracks with a suitable filler. If mould is present treat surface with bleach solution then wash off with clean water and allow to dry. Spot bare substrate in accordance with directions for new work.

 **Application**

Application

Apply two coats liberally using a full brush or roller. A 10mm regular nap roller cover will give best results. Spread paint evenly and do not overspread. Repaint of surfaces in good condition may only require one coat when colour is unchanged. Where necessary, apply a second coat. Do not expose to excessive steam in the first 48 hours.

Cleanup

Water

Coverage

Up to 16m²/litre, depending on the nature of surface. Coverage on rough or absorbent surfaces will be lower.

Recoat

Recoat after 2 hours at 25°C and 50% RH.

Stirring

Stir paint well with a 25mm wide flat stirrer in a circular lifting motion for at least 5 minutes before use.

Temperature

Do not use at temperatures below 10°C or above 35°C.
