



### Description

Taubmans Endure Interior is engineered with Nanoguard. It has an interlocking molecular structure that works to create a protective shield, so stains can be wiped away without compromising the quality of the paint or damaging the finish on your walls. It provides excellent mould and mildew protection throughout the life of the paint so you will have a cleaner and healthier home environment. This is why Taubmans Endure is the only interior paint with a 15 year guarantee\*.

### Uses

Interior walls in kitchens and bathrooms.

### Recommended for

Superior performance

### Features

Taubmans Endure has a unique interlocking molecular structure that creates a protective shield so that dirt and stains can simply be wiped away without compromising the quality of the paint.

#### Fungicide Protection

Resists mould and mildew growth.

#### Interlocking molecular structure

Protects against stains and regular washing.

#### Nanoguard

Engineered to Endure with a 15 year warranty.

### Technical

#### Colour Range

Extensive colour range. Refer Taubmans to Consumer or Architectural/Specifier Colour Systems.

#### Drying And Recoating

Normally dries in 30 minutes and may be recoated after 2 hours (at 25°C and 50% relative humidity). Note - Drying time may be lengthened in damp, cold or humid conditions.

#### Gloss Level

Low Sheen (5-10%) as per AS2311

#### Specifications met

AS3730.3

#### Washability

Superior.

#### VOC

41g/litre

### Surface Preparation

Surfaces to be painted must be clean and dry.

---

**New/Bare Work**

Seal bare wallboards with Taubmans 3in1. Seal set plaster with Prep Right (Acrylic) Plaster Sealer.

---

**Repaint**

Remove all loose and flaking paint. Wash off dirt, grease. Fill holes and cracks with a suitable filler. If mould is present treat surface with bleach solution then wash off with clean water and allow to dry. Spot bare substrate in accordance with directions for new work.

---

 **Application**

---

**Application**

Apply two coats liberally using a full brush or roller. A 10mm regular nap roller cover will give best results. Spread paint evenly and do not overspread. Repaint of surfaces in good condition may only require one coat when colour is unchanged. Where necessary, apply a second coat. Do not expose to excessive steam in the first 48 hours.

---

**Cleanup**

Water

---

**Coverage**

Up to 16m<sup>2</sup>/litre, depending on the nature of surface. Coverage on rough or absorbent surfaces will be lower.

---

**Recoat**

Recoat after 2 hours at 25°C and 50% RH.

---

**Stirring**

Stir paint well with a 25mm wide flat stirrer in a circular lifting motion for at least 5 minutes before use.

---

**Temperature**

Do not use at temperatures below 10°C or above 35°C.

---