

**Description**

A premium quality bacteria and mould resistant, long lasting wall paint which gives a uniform, smooth, flat finish. Easycoat Flat provides good washability with the capacity to hide surface imperfections. Easycoat Flat Acrylic contains ceramic pigment advanced technology to provide a washable, flat finish with high hiding power.

Uses

Walls and ceilings of living rooms, bedrooms, dining rooms and all areas where an attractive flat finish is required. For high traffic areas Easycoat Low Sheen Acrylic or Semi Gloss Acrylic may be preferred.

Recommended for

Defect hiding for walls in low traffic areas.

 **Features****Antibacterial Protection**

Microban® is an exclusive antibacterial technology that protects against growth of bacteria. Microban® technology lasts the life of the paint and will not wear out or wash off.

Ceramic Pigment

Washable, tough surface

Cost Effective

Premium quality at a competitive price

High Opacity

Excellent coverage and hiding power

Mould resistant

Microban® resists the growth of mould and mildew that according to the National Asthma Council Australia may trigger asthma symptoms, hay fever and other allergies.

Special Thickeners

Low roller spatter and ease of application

Very Flat Finish

Helps to hide surface imperfections

 **Technical****Colour Range**

Extensive colour range. Refer to Taubmans Consumer or Architectural/Specifier Colour Systems.

Drying And Recoating

Normally dries in 30 minutes and may be recoated after 2 hours (at 25°C and 50% relative humidity). Note - Drying time may be lengthened in damp, cold or humid conditions.

Gloss Level

Flat (1%) as per AS2311

Odour

Low. Ensure adequate ventilation during use.

Specifications met

APAS 0260/4 and AS3730.1 National Asthma Council Australia Sensitive Choice

VOC

Easycoat is low in Volatile Organic Compounds (VOCs) and is low odour.

Washability

Good. After 7 days EasyCoat Flat Acrylic may be carefully washed with soap and water. Do not rub or use abrasive cleaners, as a shiny spot may be left.

Early Fire Hazard Properties - AS1530.3

Ignitability Index 0 Spread of Flame Index 0 Heat Evolved Index 0 Smoke Developed Index 2

Surface Preparation

New/Bare Work

Seal bare wallboards with Easy Prep Undercoat and Wallboard Sealer or Ultraprep.

Repaint

Remove all loose and flaking paint and peeling wallpaper. Wash off dirt, kalsomine, grease or wallpaper paste. Seal kalsomine residue, undercoat aged enamel and stripped wallpaper areas with Easy Prep All Purpose Undercoat to assist adhesion. Fill holes and cracks with a suitable filler. If mould is present treat surface with bleach solution then wash off with clean water and allow to dry.

Application

Application

Apply one or two coats as required by brush, roller or spray. A 10mm regular nap roller cover or similar will give best results.

Cleanup

Water

Coverage

Up to 16m²/litre, depending on the nature of surface. Coverage on rough or absorbent surfaces will be lower.

Recoat

Recoat after 2 hours at 25°C and 50% RH

Stirring

Stir paint with a 25mm wide flat stirrer in a circular lifting motion for at least 5 minutes before use.

Temperature

Do not use at temperatures below 10°C or when humidity is excessive. Do not expose to excessive steam in the first 48 hours.
