


Description

A premium quality bacteria and mould resistant, hard wearing interior finish with excellent washability. Contains ceramic pigment to provide a tough satin finish that resists stains and dirt, making it ideal for high traffic areas.

Uses

Walls and ceilings of any areas which are subject to high traffic. Ideal for wet areas where high moisture, bacteria and mould resistance is necessary. Ideal for light commercial environments such as schools, hospitals etc.

Recommended for

High serviceability.


Features
Antibacterial Protection

Microban® is an exclusive antibacterial technology that protects against growth of bacteria. Microban® technology lasts the life of the paint and will not wear out or wash off.

Ceramic Pigment

Washable, tough surface

Cost Effective

Premium quality at a competitive price

High Opacity

Excellent coverage and hiding power

Moisture Resistance

Suitable for wet areas

Mould resistant

Microban® resists the growth of mould and mildew that according to the National Asthma Council Australia may trigger asthma symptoms, hay fever and other allergies.

Special Thickeners

Low roller spatter and ease of application


Technical
Colour Range

Extensive colour range. Refer Taubmans to Consumer or Architectural/Specifier Colour Systems.

Drying And Recoating

Normally dries in 30 minutes and may be recoated after 2 hours (at 25°C and 50% relative humidity). Note - Drying time may be lengthened in damp, cold or humid conditions.

Gloss Level

Semi Gloss (20 - 25%) as per AS2311

Odour

EasyCoat Low Sheen is low in odour.

Specifications met

APAS 0260/2 and AS3730.2 National Asthma Council Australia Sensitive Choice

Washability

Excellent

Early Fire Hazard Properties - AS1530.3

Ignitability Index 0 Spread of Flame Index 0 Heat Evolved Index 0 Smoke Developed Index 2

🔧 Surface Preparation

New/Bare Work

Seal bare wallboards with EasyPrep Undercoat and Wallboard Sealer.

Repaint

Remove all loose and flaking paint and peeling wallpaper. Wash off dirt, kalsomine, grease or wallpaper paste. Seal kalsomine residue, undercoat aged enamel and stripped wallpaper areas with Easy Prep All Purpose Undercoat to assist adhesion. Fill holes and cracks with a suitable filler. If mould is present treat surface with bleach solution then wash off with clean water and allow to dry.

🔧 Application

Application

Apply two coats by brush, roller or spray. A 7mm short nap cover will give best results.

Cleanup

Water

Coverage

Up to 16m²/litre, depending on the nature of surface. Coverage on rough or absorbent surfaces will be lower.

Recoat

Recoat after 2 hours at 25°C and 50% RH.

Stirring

Stir paint with a 25mm wide flat stirrer in a circular lifting motion for at least 5 minutes before use.

Temperature

Do not use at temperatures below 10°C or when humidity is excessive. Do not expose to excessive steam in the first 48 hours.