

Easycoat Ceiling Paint with Microban®

D305



Description

A premium quality bacteria and mould resistant paint for ceilings. Easycoat Ceiling Paint with Microban® has excellent opacity and dries to a uniform flat finish.

Uses

Ceilings in all areas particularly suited where mould, mildew and bacteria may be a problem.

Recommended for

Ceilings in all areas of the building

 **Features**

Antibacterial Protection

Microban® is an exclusive antibacterial technology that protects against growth of bacteria. Microban® technology lasts the life of the paint and will not wear out or wash off.

Mould resistant

Microban® resists the growth of mould and mildew that according to the National Asthma Council Australia may trigger asthma symptoms, hay fever and other allergies.

Special Thickeners

Low roller spatter

Very Flat Finish

Helps to hide defects

 **Technical**

Colour Range

White and a wide range of pastel colours

Drying And Recoating

Normally dries in 30 minutes and may be recoated after 2 hours (at 25°C and 50% relative humidity). Note - Drying time may be lengthened in damp, cold or humid conditions.

Gloss Level

Flat (1%) as per AS2311

Odour

Low. Ensure adequate ventilation during use.

Specifications met

APAS 0260/4 and AS 3730.1 National Asthma Council Australia Sensitive Choice

 **Surface Preparation**

New/Bare Work

Seal bare plasterboard with Easycoat Prep Undercoat and Wallboard Sealer with Microban® or Ultraprep. Seal aged set plaster with PrepRight Plaster Sealer thinned 20%.

Repaint

Remove all loose and flaking paint back to a firm surface. Wash off dirt, kalsomine and grease. Seal kalsomine residue, undercoat aged enamel with PrepRight Traditional Undercoat to assist adhesion. Fill holes and cracks with a suitable filler, sand smooth and seal with Easy Prep Undercoat or Ultraprep. If mould is present treat with bleach.

Application

Application

Apply two coats liberally with a brush, roller or spray. One coat is usually sufficient when repainting with the same colour. A 10mm regular nap roller cover gives best results.

Cleanup

Water

Coverage

Up to 16 square meters per litre depending on the nature of the surface. Spread rate on rough or absorbent surfaces will be lower.

Directions

Customer service contact # 0800 131 686 Fax # +61 2 9725 7804 Emergency contact # 0800 154 666

Recoat

Recoat after 2 hours at 25°C and 50% RH.

Stirring

Stir paint with a 25mm flat stirrer in a circular lifting motion for at least 5 minutes before use.

Temperature

Do not apply at temperatures below 10°C, over 35°C or when humidity is excessive.