

**Description**

A 100% acrylic high performance preparatory product for interior walls and trims. The unique formula is low in VOC for maximum indoor air quality. Pure Performance Precoat contains Microban, which inhibits the growth of harmful bacteria, mould mildew and fungus enabling a cleaner safer built environment.

**Uses**

Primer sealer undercoat for interior use. Low odour and low VOC make Pure Performance ideal for new construction and repaint.

**Recommended for**

Primer sealer undercoat for new work and repaint.

 **Features****Antibacterial Protection**

Microban® is an exclusive antibacterial technology that protects against growth of bacteria. Microban® technology lasts the life of the paint and will not wear out or wash off.

**High Opacity & Filling**

Excellent coverage and appearance

**Low VOC**

<5g/litre VOC, suitable for Green Building Council projects, low odour

**Mould resistant**

Microban® resists the growth of mould and mildew that according to the National Asthma Council Australia may trigger asthma symptoms, hay fever and other allergies.

 **Technical****Specifications met**

APAS 0172

**VOC**

<5g/litre. Meets GBC requirement.

**Colour Range**

White, and tints from white.

**Spread Rate**

Up to 14sqm/litre. Coverage will be lower on rough or absorbent surfaces.

**Drying And Recoating**

Touch dry in 30 minutes. Recoat in 2 hours at 25°C. Allow 4 hours in cooler or humid conditions.

 **Surface Preparation**

Surfaces must be clean, dry and free from all surface contamination. Wash down the surface with detergent, followed by a rinse with clean water. Treat mould with bleach then rinse with fresh water. Fill in surface defects such as cracks or holes with a suitable filler, putty or sealant. Avoid using masking tape on wall and ceiling paints.

**New/Bare Work**

Plasterboard, Masonry & Timber – Undercoat with Pure Performance Precoat.

**Repaint**

Scrape and sand down surface to remove all loose and flaking paint. Spot bare areas with Pure Performance Precoat. Sand glossy or enamel surfaces thoroughly with 240 grit paper and undercoat with Pure Performance Precoat as required. Ensure an even surface when painting over patchy or contrasting colours by applying one coat of Pure Performance Precoat.

 **Application**

Stir paint well in a circular lifting motion for 5 minutes before use with a broad flat paddle. Apply one coat by using a 12mm roller and good quality brush. Extra coats may be required for application by brush only. It is also important to avoid using poor quality or worn rollers and brushes as they can adversely affect the final finish. Spray Application. Airless Spray or HVLP. Thin up to 10%.

**Cleanup**

Water, away from drains.

**Temperature**

Do not paint when temperature is below 10°C, or above 35°C.